


EventDeck 1

MODEL ED1 PRODUCT SPECIFICATIONS



- Module Size:** **Width:** 4" / 10.16 cm / 101.6 mm
 Length: 12" / 30.48 cm / 304.80 mm
 3 connected modules = 12" x 12" / 304.8 mm x 304.8 mm
 Thickness: 3/4" Tall / 1.91 cm / 19.05 mm
- Module Weight:** 0.27 lbs. / 4.3 oz. / 0.12 kg. / 122 grams
 Per Square Foot: 0.81 lbs. / 12.96 oz. / 0.37 kg. / 367.41 grams
 Per Square Meter: 8.72 lbs. / 3.95 kg.
- Material:** High-impact polypropylene co-polymer. UV Inhibitors added.
- Fire Rating:** UL 94HB (Underwriters Laboratory Yellow Card Number)
 This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.

 ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)
 – passed test
 * Testing reports available for fire ratings
- Hot Wire**
- Ignition Rating:** 3
- Melting Point:** 324 Fahrenheit / 162 Celsius
 Operating Range: -10° F to 150°F / -23.33° C to 65.56° C
- Support Structure:** Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads. There are no open spans (without ribs) greater than 2.125".
- Weight Loading:** 8,000 lbs sq ft static load, solid sub-surface. Varies depending on subsurface.
- Ground Surfaces:** EventDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.
- Shipping:** 40" x 48" Pallet: up to 1,000 sq ft
 463L Pallet: 7,776 sq ft
 20' Ocean Container: 20,000 sq ft
 40' Ocean Container: 40,000 sq ft

 Note: High cube container loads can be loaded with additional product.

(Continued)

- Functional Features:**
- a) Sections are designed to roll up for easy installation, removal, storage and transport.
 - b) Individual modules interconnect to form larger flooring sections.
 - c) Connection system allows for installation and disassembly without the need for connection or separation tools.
 - d) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
 - e) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
 - f) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Grass Protection

Features (ED1):

- a) Modules feature an integrated moisture canopy which allows for moisture retention.
- b) EventDeck features direct-from-the-top drainage holes that provide drainage, ventilation, air, and small amounts of light to grass below.
- c) Underside is specially designed to protect grass and other sensitive surfaces by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.

Warranty: 3-year warranty against manufacturer's defects.

National Stock #: 8340-01-525-4069

EVENTDECK ACCESSORIES SPECIFICATIONS

Edging

Specifications: Edging size is 3" x 12" x 3/4" (tapered). Edging is designed to attach to flooring modules both lengthwise and widthwise, providing a gradual tapered edge. Edging extends flat 1" from end of flooring module and then slopes down to ground over a 2" span.



17826 Canterbury Rd. :: Cleveland, OH 44119
Phone (216) 481-0755 :: Fax (216) 481-7558
www.CrowdControlDepot.com

Toll-Free (800) 235-1810