

# EventDeck 2

## MODEL ED2 PRODUCT SPECIFICATIONS



- Module Size:**      **Width:** 4" / 10.16 cm / 101.6 mm  
                          **Length:** 12" / 30.48 cm / 304.80 mm  
                          3 connected modules = 12" x 12" / 304.8 mm x 304.8 mm  
                          **Thickness:** 3/4" Tall / 1.91 cm / 19.05 mm
- Module Weight:**    0.27 lbs. / 4.3 oz. / 0.12 kg. / 122 grams  
                          Per Square Foot: 0.81 lbs. / 12.96 oz. / 0.37 kg. / 367.41 grams  
                          Per Square Meter: 8.72 lbs. / 3.95 kg.
- Material:**            High-impact polypropylene co-polymer. UV Inhibitors added.
- Fire Rating:**        UL 94HB (Underwriters Laboratory Yellow Card Number)  
                          This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.  
  
                          ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)  
                          – passed test  
                          \* Testing reports available for fire ratings
- Hot Wire**
- Ignition Rating:**    3
- Melting Point:**     324 Fahrenheit / 162 Celsius  
                          Operating Range: -10° F to 150°F / -23.33° C to 65.56° C
- Support Structure:** Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads. There are no open spans (without ribs) greater than 2.125".
- Weight Loading:**    8,000 lbs sq ft static load, solid sub-surface. Varies depending on subsurface.
- Ground Surfaces:** EventDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.
- Shipping:**            40" x 48" Pallet:                    up to 1,000 sq ft  
                          463L Pallet:                        7,776 sq ft  
                          20' Ocean Container:            20,000 sq ft  
                          40' Ocean Container:            40,000 sq ft  
  
                          Note: High cube container loads can be loaded with additional product.

(Continued)

- Functional Features:**
- a) Sections are designed to roll up for easy installation, removal, storage and transport.
  - b) Individual modules interconnect to form larger flooring sections.
  - c) Connection system allows for installation and disassembly without the need for connection or separation tools.
  - d) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
  - e) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
  - f) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

**Warranty:** 3-year warranty against manufacturer's defects.

**National Stock #:** 8340-01-525-4069

## **EVENTDECK ACCESSORIES SPECIFICATIONS**

### **Edging**

**Specifications:** Edging size is 3" x 12" x 3/4" (tapered). Edging is designed to attach to flooring modules both lengthwise and widthwise, providing a gradual tapered edge. Edging extends flat 1" from end of flooring module and then slopes down to ground over a 2" span.



17826 Canterbury Rd. :: Cleveland, OH 44119  
Phone (216) 481-0755 :: Fax (216) 481-7558  
[www.CrowdControlDepot.com](http://www.CrowdControlDepot.com)

**Toll-Free (800) 235-1810**