

UltraDeck

MODEL EDU PRODUCT SPECIFICATIONS

Module Size:	Width: 24" / 60.96 cm / 609.6 mm Length: 12" / 30.48 cm / 304.80 mm Thickness: 1.375" Tall / 3.4925 cm / 34.925 mm
Module Weight:	2.88 lbs. / 46.08 oz. / 1.306 kg. / 1306 grams Per Square Foot: 1.44 lbs. / 23.04oz. / 0.653 kg. / 653 grams Per Square Meter: 15.50 lbs. / 7.03 kg.
Material:	High-impact polypropylene co-polymer. UV Inhibitors added.
Fire Rating:	UL 94HB (Underwriters Laboratory Yellow Card Number) This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers. ASTM 2859 (Flammability of Finished Texture Floor Covering Materials) – passed test * Testing reports available for fire ratings
Hot Wire Ignition Rating:	3
Melting Point:	324 Fahrenheit / 162 Celsius Operating Range: -10° F to 150°F / -23.33° C to 65.56° C
Support Structure:	Flooring module incorporates multi-directional structural support ribbing, allowing for distribution of weight and loads.
Weight Loading:	20,000 lbs sq ft static load, solid sub-surface. Varies depending on subsurface.
Ground Surfaces:	UltraDeck is designed to be used with little ground preparation over grass, gravel, sand, soil, concrete, asphalt, ice, snow, mud, synthetic turf, rubberized tracks, and other standard surfaces.
Shipping:	40" x 48" Pallet: up to 816 sq ft 463L Pallet: 3,312 sq ft 20' Ocean Container: 8,160 sq ft 40' Ocean Container: 16,320 sq ft Note: High cube container loads can be loaded with additional product. 48' Truck: 19,684 sq ft 53' Truck: 21,216 sq ft

(Continued)

Functional

Features:

- a) Individual modules interconnect to form larger flooring sections.
- b) Connection system allows for installation and disassembly without the need for connection or separation tools.
- c) Modules feature integrated, multi-directional cable channels on the underside of each tread, for running power and communication wiring or rope lighting.
- d) Modules are designed to allow 90-degree rotation and still connect. Module can be connected in both directions and at any module connection point, allowing greater flexibility in floor design.
- e) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

Warranty: 3-year warranty against manufacturer's defects.

National Stock #: 8340-01-525-4069

UltraDeck ACCESSORIES SPECIFICATIONS

Edging

Specifications: Edging size is 3" x 12" x 3/4" (tapered). Edging is designed to attach to flooring modules both lengthwise and widthwise, providing a gradual tapered edge.



17826 Canterbury Rd. :: Cleveland, OH 44119
Phone (216) 481-0755 :: Fax (216) 481-7558
www.CrowdControlDepot.com

Toll-Free (800) 235-1810