

# HexaDeck

## MODEL HD      PRODUCT SPECIFICATIONS

- Module Size:** 3.00 sq. ft. in hexagonal configuration - 26" wide at widest point  
Height: 1.9"
- Module Weight:** 6 lbs. / 96 oz. / 2.72 kg. / 2772 grams  
Per Square Foot: 2 lbs. / 32 oz. / 0.91 kg. / 907 grams  
Per Square Meter: 21.5 lbs. / 9.75 kg.
- Material:** High-Density Polyethylene. UV Inhibitors added.
- Fire Rating:** UL 94HB (Underwriters Laboratory Yellow Card Number)  
This test signifies that this product does not flare up when exposed to an open flame and has a slow burn rate of 2" per minute for a 2" wide, 0.5 millimeter thickness test sample. EventDeck meets applicable standards for temporary floor covers.  
  
ASTM 2859 (Flammability of Finished Texture Floor Covering Materials)  
– passed test  
  
\* Testing reports available for fire ratings
- Hot Wire Ignition Rating:** 3
- Melting Point:** 324 Fahrenheit / 162 Celsius
- Support Structure:** Flooring module incorporates multi-directional, concentric, structural support ribbing, allowing for distribution of weight and loads.  
Reinforcement ribbing width is 0.14" (over 1/8").
- Weight Loading:** 30,000 lbs sq. ft. static load, solid sub-surface.  
Suitable for light and heavy pedestrian and vehicle use on multiple ground surfaces.
- Functional Features:**
- a) Tiles are designed to nest into each other, locking each tile down and together using a unique over-and-under connection system
  - b) Individual modules interconnect to form larger flooring sections. Sections can be added to any side of the HexaDeck module.
  - c) Connection system allows for assembly and disassembly without the need for separation tools. There are no loose parts -- each tile is a complete piece and requires no additional pieces to function alone or in conjunction with adjacent sections.
  - d) Tile features diamond-plate finish for added slip resistance and drainage holes to prevent water build-up.

*(Continued)*

**Grass Protection**

**Features:**

- a) Tiles feature an integrated moisture canopy that allows for moisture retention.
- b) HexaDeck incorporates drainage holes that provide ventilation, air and small amounts of light to grass below.
- c) Underside is specially designed to protect grass by distributing weight across multiple support ribs. No sharp, unsupported edges exist to damage grass or synthetic turf.
- d) Modules canopy is raised 1.85 inches off of ground surface.
- e) Modules do not have any submerged channels into which debris or dirt can enter from the top surface, and are easy to clean and maintain.

**Warranty:**

3-year warranty against manufacturer's defects.



17826 Canterbury Rd. :: Cleveland, OH 44119  
Phone (216) 481-0755 :: Fax (216) 481-7558  
[www.CrowdControlDepot.com](http://www.CrowdControlDepot.com)

**Toll-Free (800) 235-1810**